

FH2018-X-AQ series

Faucet Water Filter Advanced Drinking Water Filtration

PRODUCT FEATURES

- Advanced drinking water filtration system that works with tap water
- · Remove contaminants while improving taste and odor
- Installation is simple and non-permanent
- Filter installed in minutes is ready to use and require no plumbing modifications
- · Changing the filter cartridge is easy and requires no tools
- Simple turn the dial to switch between filtered and unfiltered water
- Compatible with FC2018-2-AQ and FC2018-1-AQ cartridges

PRODUCT APPLICATIONS

- 1. Domestic installation
- 2. For drinking and cooking
- 3. Compact and apartment size
- 4. Elegant filter design
- 5. User firendly

PRODUCT PACKAGING



Set includes

- 1. Faucet water filter
- 2. Replacement cartridge
- 3. 10 diverter adapter options to fit all standard faucets
- 4. Color box H770 x L297 x W209 mm





Improves taste of water



Doesn't require any tools for installation



OPTIONAL TAP OR PURE WATER



10 ADAPTERS + REPLACEMENT CARTRIDGE

pure wate



PRODUCT SPECIFICATIONS

Product Name: Faucet Water Filter

Product Model: FH2018-1-AQ/ FH2018-2-AQ

Product Size: 172 x 8 x 68 mm

Product Name: Replacement Cartridge **Product Model:** FC2018-1-AQ/ FC2018-2-AQ

Product size: 60 x 105 x 63 mm

Water Source: City water

Filtration Precision: 0.01 micron **Filtration methods:** Physical filtration

Suitable Ambient: 5 ~ 40°C Suitable pressure: 0.1-0.4MPA Suitable temperature: 5 ~ 45°C Pure Water Flow: 1.5-2.SL/min

FC2018-2-AQ | FC2018-1-AQ **PP Sediment** removes: dust, sand, silt, dirt, PΡ **Activated Carbon** Sediment improves: water taste and odor Ion Exchange Resin **Activated** water softening and purification Carbon and ION **Ultra Filtration Membrane** removes: 99.99 Bacteria, Cadium, Lead, Iron, Cryptosporidium and Giardia Cysts DD **Sediment**

ACCESSORIES



10 Universal Adapters



Faucet Filter Box



Replacement Cartdridge

PRODUCT INSTALLATION

This filter is equipped with 10 thread connectors, 5 internal thread connectors, 3 external thread connectors, 1 metal conversion connector and 1 universal conversion connector. Determinate adapter needed, find corrected adapter attached and screw it to the faucet.

1. Unscrew the faucet aerators and take out the gasket.





2. Put the gasket into the groove connector and rotate the connector to the tap. If all above conversion connector don't match the tap, can use the universal conversion connector to install.









Before first use, turn faucet filter to filtration setting and flush filter. There may be a small amount of black residue in water when the faucet filter is set to the filtration setting. Continue to flush, the filter is ready for.

WARNINGS

FAUCETS IN WHICH THE FAUCET FILTER CANNOT BE INSTALED

- 1. Faucet front end to lower edge is 15mm or less.
- 2. Faucet front end with aspersed type shower head.
- 3. Faucet front end abnormality.
- 4. Faucet front end diameter and conversion connector don't match.
- 5. Faucet front end diameter is 25mm or more.
- 6. Equipped with sensor faucets.

ATTENTION!

- 1. Do not take apart or modified the unit without authorization.
- 2. Do not put in contact with corrosive substances.
 - 3. Do not put in contact with fire.
- The faucet filter cannot be used in less than 4°C environment! Prevent cracks and leaks caused by freezing water inside pipe.
 - 5. because of low temperatures.